



**CONTACT INFORMATION:**

4550 145TH STREET  
CHIPPEWA FALLS, WI 54729

PHONE: (715) 723-8444  
CELL: (715) 797-8989  
EMAIL: STOPAGRIND@YAHOO.COM



*Series 200 Decorative wall, planter, and curb deterrents*

**90 DEGREE WALL  
DETERRENT**

**45 DEGREE WALL  
DETERRENT**

**RADIUS WALL  
DETERRENT**

**SEAT WALL  
DETERRENT**



Our low profile skateboard deterrents and stops can be used on walls, planters, benches, picnic tables and curbs. The series 200 is our most popular deterrent design because it is completely rounded and bull nosed therefore limiting the inconvenience to the general public.

They are mounted by drilling two holes for the two anchors and screws. Every one of StopAGrind's deterrents are custom machined from a solid block of aluminum. This allows us to match any contour you may need at no additional cost to you. For your convenience we do offer packages with and without the fasteners.

**INSTALLATION AS SIMPLE AS 123**

- Drill two holes 1/2" diameter into the base material to a depth equal to, or slightly deeper than, the length of the expansion shield.
- Place the single expansion anchor, nut end first, into the hole. The top end of the anchor should be flush or slightly below the base material surface.
- Place the object to be fastened over the anchor in the base material and bolt into place. The bolt should engage 2/3 of the threads of the anchor.

Anchor Size	Anchor Length	Hole Size	Bolt Dia.	Pull-Out Concrete
1/4"	1-5/16"	1/2"	1/4"	1600 lbs.

**Series 200 Product Specs:**

- 6061 ALUM.
- Length 3.0"
- Diameter 1.0"
- Screw size 1/4-20



**Concrete Anchor**



**Tamper Res.**



**Installation Bit**